



Part No.	Housing Color
999-11-058301	BLACK
999-11-058311	RED

Specification:

Contact Resistance: 30m Ohm Max. At AC 100mA Max.1KHz.

Insulation Resistance: 100M Ohm Min. At 500V DC.

Rated Voltage And Current: DC 12V,2A Max.

Dielectric Withstanding Voltage: 500VAC At 60Hz For 1 Minute.

Durability (Life Test): 4000 Cycles.

Insertion Force: 0.3~3.0 Kg.

Extraction Force: 0.3~3.0 Kg.

NO.	NAME	MATERIAL	FINISH	Q'TY
1	BARREL	BRASS T:0.4	NICKEL PLATED	1
2	SPRING TERMINAL	PHOS. BRONZE T:0.30	TIN PLATED	1
3	TERMINAL	BRASS T:0.4	TIN PLATED	1
4	HOUSING	PBT G.F.	BLACK / RED	1

TOLERANCE		UNITS : mm	OLD PART NO.		TITLE	
.0	=±.30				RCA JACK	
.00	=±.20	SCALE NONE	DRAWER 胡雨婷		DRAW NO. 999-11-0583x1	
.000	=±.XXX		SHEET 1 OF 1		DRAW NO. 999-11-0583x1	
.0000=±.		SIZE A4		NEW PART NO. 999-11-0583x1		
ANG.=±3'				APP'D		
A	RELEASE	2014/08/07			PINREX TECHNOLOGY CORP.	
REV.	DESCRIPTION	DATE			DRAW NO. 999-11-0583x1	

