

THICKNESS	A
0.8t ~ 1.0t	25.4
1.0t ~ 1.2t	25.5
1.2t ~ 1.5t	25.6
2t	25.7
3t	25.7



SPECIFICATION:


1. INSULATION RESISTANCE: OVER 100MΩ 500V DC.
2. DIELECTRIC STRENGTH: 2000V AC ONE MINUTE.
3. Body Material: Black Glass-Fiber Thermoplastic . UL 94V-2~0

Rating:AC 15A 250V	
Mark	Safety Regulation
cULus	cULus
Rating:AC 10A 250V	
Mark	Safety Regulation
	VDE
	CCC
	ENEC

IMPORTANT THIS DRAWING FOR REFERENCE ONLY 注意：此圖只供參考用



富灣(佛岡)五金電器有限公司
RICH BAY INT'L LTD.
 廣東省清遠市佛岡縣城南工業區
 South Town Industrial Area of Fogong County
 Qing Yuan City Guangdong Province,China
 TEL:0763-4289946 FAX:0763-4288096



DRAWN BY

UNIT	UNIT QTY	SCALE
mm	1	1:1
DRAWN BY 李 2010.3.26 小英		APPROVED BY 羅 2010.3.26 士凱

TOLERANCE	PRODUCT NO.	REV
X.XX±0.1 XX.XX±0.2 XXX.XX±0.3	R-302SN(B00)	
ID NO	INTERIM NO.	C
10032606Q	710-186	
DESCRIPTION	NEW NO.	