



**SPECIFICATION:**

1. Insulation Resistance: Over 100MΩ at 500V DC.
2. Dielectric strength: 2000V AC 1 Minute.
3. Body Material: Thermoplastic 94V-2~V-0.
4. Withdrawal force: 30N~50N

Rating:AC 15A 250V	
Mark	Safety Regulation
	CULUS
Rating:AC 10A 250V	
Mark	Safety Regulation
	VDE
	ENEC
	CCC



DRAWING:C:DG\NEW-R\T-台北\R-302SN-H\R-302SN-H(07).DWG

<b>富灣股份有限公司</b> RICH BAY COMPANY LTD. 台北縣樹林市東興街57號 NO. 57, Tung Hsing St., Shu-Lin Town, Taipei Hsien, Taiwan, R. O. C. TEL:886-2-86867781~4 FAX:886-2-86867780 http://www.richbay.com.tw	 DRAWN BY  106.12.05 林文啟	UNIT	UNIT QTY	SCALE	TOLERANCE X.XX±0.1 XX.XX±0.2 XXX.XX±0.3	PRODUCT NO. R-302SN-H(07)	REV
		mm	1	1:1			
		APPROVED BY	 106.12.06 張育誠	ID NO. 171205A04			
		DESCRIPTION	NEW NO.				A