



**MATERIAL**

Insulator : 30% Glass fiber PBT  
Contact Pin : Brass

**SPECIFICATION**

Current Rate : 3 AMP  
Insulation Resistance : 5000MΩMin. at DC 500V  
Contact Resistance : 20mΩMax. at DC 100mA  
Dielectric Voltage : AC 500V for one minute  
Operation Temperature : -40°C to + 105°C

211-7 2- xx G B xx  
1 2 3 4 5

1. 1: Single row
2. 2: Dual rows
3. G: Gold flash
- S: Selective
- T: Tin plated
4. B: Black Insulator
- W: White Insulator
5. Pinrex internal code.

CODE	DIM A	DIM B	DIM C
211-72-xxGB01	6.00	3.00	3.90
211-72-xxGB02	6.00	4.00	3.90

If you need other dimensions, please fill out Dim A/B/C or contact our sales representatives.

DIM A	DIM B	DIM C

POLES	DIM E	POLES	DIM E
		21	50.80
2	2.54	22	53.34
3	5.08	23	55.88
4	7.62	24	58.42
5	10.16	25	60.96
6	12.70	26	63.50
7	15.24	27	66.04
8	17.78	28	68.58
9	20.32	29	71.12
10	22.86	30	73.66
11	25.40	31	76.20
12	27.94	32	78.74
13	30.48	33	81.28
14	33.02	34	83.82
15	35.56	35	86.36
16	38.10	36	88.90
17	40.64	37	91.44
18	43.18	38	93.98
19	45.72	39	96.52
20	48.26	40	99.06

				<p><b>TOLERANCE</b></p> <p>.0 =±.30</p> <p>.00 =±.20</p> <p>.000 =±.XXX</p> <p>.0000=±.</p> <p>ANG.=±3'</p>		<p>UNITS : mm</p>		<p>OLD PART NO.</p> <p>PH1R-2xxGB A/B/C</p>		<p>TITLE</p> <p>PIN HEADER 2.54*2.54mm RIGHT ANGLE TYPE, DUAL ROWS (GP)</p>		<p>頻銳科技股份有限公司 PINREX TECHNOLOGY CORP.</p>
A	RELEASE	2004/02/27		SCALE	SIZE	SHEET	REV.	APP'D	NEW PART NO.	DRAW NO.		
REV.	DESCRIPTION	DATE		NONE	A4	1 OF 1	<b>A</b>		211-72-xxGBxx	211-72(PH1R-2)		