



ITEM	DESCRIPTION	MATERIAL	FINISHED Q'TY
1	SHELL	ZINC ALLOY	NICKEL 1
2	INSULATOR (1)	P.P. UL 94HB	1
3	CONTACT (2)	BRASS	GOLD 1
4	OUTER CONTACT	BRONZE	NICKEL 1
5	GASKET	RUBBER	1
6	SPRING WASHER	SK-5	NICKEL 1
7	RETAINING WASHER	BRONZE	NICKEL 1
8	CONTACT (1)	P. BRONZE	GOLD 1
9	LOCK WASHER	BRASS	1
10	INSULATOR (2)	P.P. UL 94HB	2
11	BODY	ZINC ALLOY	NICKEL 1

NOTES:

1. NOMINAL IMPEDANCE 50 OHMS.
2. FREQUENCY RANGE: 0-4 GHz.
3. MAX PEAK VOLTAGE: 500V.
4. INSULATION RESISTANCE: 5000 MEGOHMS MIN.
5. DIELECTRIC WITHSTANDING VOLTAGE: 1500 VOLTS RMS.
6. CENTER CONTACT ENGAGEMENT & SEPARATION FORCE:
 - A. Engagement force: 0.9 kgs minimum
 - B. Separation force: 78 grams minimum