



Recommand PCB Layout

Specifications

Voltage Rating: 250V AC/DC

Current Rating: 7A AC/DC

Contact Resistance: 20mΩmax.

Withstanding Voltage: 1500V AC/minute.

Insulation Resistance: 1000MΩ min.

Temperature Range: -25°C~+85°C

Material

Circuits: 2~14

Insulator: Nylon 66 UL 94V-2

Contact: Brass

731-7 1-xx T W 08
 1 2 3 4 5

1. 5: Normal parts
- 7: Green Product
- 9: Green Product High Temp
2. No. of contacts per row
3. G: Gold flash
- T: Tin plated
4. S: Crystal insulator
- W: Nature Color Insulator
5. Pinrex internal code.

Poles	A	B
2	3.96	7.92
3	7.92	11.88
4	11.88	15.84
5	15.84	19.80
6	19.80	23.76
7	23.76	27.72
8	27.72	31.68
9	31.68	35.64
10	35.64	39.60
11	39.60	43.56
12	43.56	47.52
13	47.52	51.48
14	51.48	55.44

		TOLERANCE		UNITS : mm		OLD PART NO.		TITLE	
		.0 =±.30		UNITS : mm		DRAWER		3.96mm HEADER DIP TYPE	
		.00 =±.20		SCALE NONE		Bindy		NEW PART NO.	
		.000 =±.XXX		SIZE A4		SHEET 1 OF 1		731-71-xxTW08	
A RELEASE		2006/04/14		ANG.=±3'		REV. A		APP'D	
REV. DESCRIPTION		DATE						PINREX TECHNOLOGY CORP.	
								DRAW NO. 731-71-xxTW08	

