



MATERIAL

Insulator : Nylon 66
 Contact Pin : Phosphor Bronze
 Contact Plated : Tin Plated

SPECIFICATION

Current Rate : 7 AMP
 Dielectric voltage : 250V(AC)
 Insulation Resistance : 1000MΩMin
 Contact Resistance : 10mΩMax
 Operation Temperature : -40°C to +105°C

759-72-xx W 001
 1 2 3 4

- 1. 5: Normal parts
- 7: Green Product
- 9: Green Product High Temp
- 2. No. of contacts per row
- 3. W: White insulator
- 4. Pinrex internal code.

CIRCUITS	DIM A	DIM B
2	5.00	10.00
3	10.00	15.00
4	15.00	20.00
5	20.00	25.00
6	25.00	29.90
7	30.00	34.90
8	35.00	39.90
9	40.00	44.90
10	45.00	49.90

		TOLERANCE		 UNITS : mm		OLD PART NO.		TITLE	
		.0 =±.30		SCALE		DRAWER		5.0mm HOUSING AND TERMINAL	
		.00 =±.20		NONE		Naomi			
		.000 =±.XXX		SIZE		SHEET		NEW PART NO.	
		.0000=±.		A4		1 OF 1		759-75-xxW001	
		ANG.=±3'				REV.		DRAW NO.	
A		2006/03/17				APP'D		759-75-xxW001	
RELEASE		DATE						頻銳科技股份有限公司	
DESCRIPTION								PINREX TECHNOLOGY CORP.	
								DRAW NO. 759-75-xxW001	