



Recommand PCB Layout

Specifications

Voltage Rating: 250V AC/DC

Current Rating: 7A AC/DC

Contact Resistance: 20mΩ

Withstanding Voltage: 1500V AC/minute.

Insulation Resistance: 1000M

Temperature Range: -25°

Material

Circuits: 2~14

Insulator: Nylon 66 UL 94V-2

Contact: Brass

731-7 2-xx T W 08
 1 2 3 4 5

- 1. 5: Normal parts
- 7: Green Product
- 9: Green Product High Temp

2. No. of contacts per row

3. G: Gold flash

T: Tin plated

4. S: Crystal insulator

W: Nature Color Insulator

5. Pinrex internal code.

Poles	A	B
2	3.96	7.92
3	7.92	11.88
4	11.88	15.84
5	15.84	19.80
6	19.80	23.76
7	23.76	27.72
8	27.72	31.68
9	31.68	35.64
10	35.64	39.60
11	39.60	43.56
12	43.56	47.52
13	47.52	51.48
14	51.48	55.44

			<p>TOLERANCE</p> <p>.0 = ±.30</p> <p>.00 = ±.20</p> <p>.000 = ±.XXX</p> <p>.0000 = ±.</p> <p>ANG. = ±3°</p>		<p>UNITS : mm</p>		<p>OLD PART NO.</p>		<p>TITLE</p> <p>3.96mm HEADER R/A TYPE</p>		<p>頻銳科技股份有限公司</p> <p>PINREX TECHNOLOGY CORP.</p>	
A	RELEASE	2006/04/14	SCALE	SIZE	SHEET	REV.	APP'D	NEW PART NO.	DRAW NO.		DRAW NO.	
REV.	DESCRIPTION	DATE	NONE	A4	1 OF 1	A		731-72-xxTW08	731-72-xxTW08		731-72-xxTW08	