



### SPECIFICATION

SHELL : Tin plated Shell

CONTACT :

Gold plated over nickel , Brass

INSULATOR :

PBT Glass fibre reinforced UL 94 V0

CURRENT RATING : 3 AMP

DIELECTRIC STRENGTH : 1000V AC for one minute

INSULATOR RESISTANCE : 1000M Min $\Omega$ at 500V DC

TEMPERATURE : -55°C ~ +105°C

993- 8 3 - 1M 99 2 1  
 1 2 3 4 5

1. 3: Tray
2. 1M: Mini gender changer
3. 99: 9P to 9P
4. 2: Metal Female to Female
5. Pinrex internal code.

Green Product

		TOLERANCE				OLD PART NO.		TITLE	
		.00 = ±.XX .000 = ±.XXX .0000 = ±. ANG. = ±X'		UNITS : mm		DRAWER <i>Naomi</i>		CHECK	
A RELEASE		2007/07/24		SCALE NONE SIZE A4		SHEET 1 OF 1 REV. <b>A</b>		APP'D	
REV. DESCRIPTION		DATE				NEW PART NO. 993-83-1M9921		DRAW NO. 993-83-1M9921	

頻銳科技股份有限公司  
PINREX TECHNOLOGY CORP.