



SPECIFICATION

SHELL :

Steel,Zinc plated or Tin plated

PIN CONTACT :

Gold plated over nickel

INSULATOR :

PBT Glass fibre reinforced UL 94 V0

CURRENT RATING :

5 AMP

DIELECTRIC STRENGTH :

1000V for one minute

INSULATOR RESISTANCE :

1000M Min at 500V DC

TEMPERATURE :

-55°C ~ +105°C

993- 8 $\frac{3}{1}$ - $\frac{1M}{2}$ $\frac{11}{3}$ $\frac{1}{4}$ $\frac{1}{5}$

1. 3: Tray

2. 1M:gender changer

3. 11: 15P to 15P

4. 1: Metal Male to Male

5. Pinrex internal code.

		TOLERANCE		 UNITS : mm		OLD PART NO.		TITLE	
		.00 =±.XX		SCALE NONE		DRAWER <i>Age</i>		MINI CHANGER METAL	
		.000 =±.XXX		SIZE A4		CHECK		15M/15M GP TRAY	
A RELEASE		2010/03/01		SHEET 1 OF 1		APP'D		NEW PART NO.	
REV. DESCRIPTION		DATE		ANG.=±X'		REV. A		993-33-1M1111	
								頻銳科技股份有限公司 PINREX TECHNOLOGY CORP.	
								DRAW NO. 993-83-1M1111	