

SPECIFICATION

SHELL :

Steel,Zinc plated or Tin plated

PIN CONTACT :

Gold plated over nickel

INSULATOR :

PBT Glass fibre reinforced UL 94 V0

CURRENT RATING :

5 AMP

DIELECTRIC STRENGTH :

1000V for one minute

INSULATOR RESISTANCE :


1000M Min at 500V DC

TEMPERATURE :

-55°C ~ +105°C

993- 8 $\frac{3}{1}$ - $\frac{1M}{2}$ $\frac{22}{3}$ $\frac{2}{4}$ $\frac{1}{5}$

- 1. 3: Tray
- 2. 1M:gender changer
- 3. 22: 25P to 25P
- 4. 2: Metal Female to Female
- 5. Pinrex internal code.

		TOLERANCE		UNITS : mm		OLD PART NO.		TITLE	
		.00 =±.XX		SCALE NONE		DRAWER <i>Age</i>		MINI CHANGER METAL	
		.000 =±.XXX		SIZE A4		CHECK		25F/25F GP TRAY	
A RELEASE		2010/03/01		SHEET 1 OF 1		APP'D		NEW PART NO.	
REV. DESCRIPTION		DATE		ANG.=±X'		REV. A		993-33-1M2221	
								 頻銳科技股份有限公司 PINREX TECHNOLOGY CORP.	
								DRAW NO. 993-83-1M2221	