


Panel Cut-out Dimensions



Rating :

UL: U16WR  16A(RES) 125VAC
12A(IND) 125VAC

VDE: 250V~   10(6)A
6(4)A 5E4 T85/55

Remark : TAB TERMINAL NOT FOR SOLDERING

Panel Thickness (mm/inch)	DIM X ^{+0.1} (mm/inch)	DIM Y ^{±0.1} (mm/inch)
0.5~1.2 (.02~.05)	19.4 (.764)	13.1 (.516)
1.2~2.0 (.05~.08)	19.7 (.775)	
2.0~3.0 (.08~.12)	20.0 (.787)	

ISSUED	SPECIFICATION (INITIAL)	TITLE: ROCKER SWITCH 1P1T			
	RATING: AC 125V 16A	MODEL NO: U16WR-11N01-R1(00)-00			
	CONTACT RESISTANCE: MAX. 30mΩ	UNIT: mm	DWN	L.Z.WANG	1.7.2003
	INSULATION RESISTANCE: 500MΩ at 500V DC	SCALE: 2 : 1	CHK'D		
	WITHSTAND VOLTAGE: AC 1000V for 1 min	TOLERANCE: ±0.2	APPD.		
	OPERATION FORCE: 600±250g	DRWG NO: A10419-02			
	SWITCHING LIFE: 10000 Cycles(6-10c/m loading)	PROMOTIVE INDUSTRIAL CO., LTD. HONG KONG			
BY:					
DATE:					