


NPN SILICON PLANAR EPITAXIAL TRANSISTORS

**BC237,238, A,B,C
 BC239, B,C**



**TO-92
 Plastic Package**
 For Lead Free Parts, Device
 Part # will be Prefixed with
 "T"

Amplifier Transistors

ABSOLUTE MAXIMUM RATINGS (T_a=25°C)

DESCRIPTION	SYMBOL	BC237	BC238	BC239	UNITS
Collector Emitter Voltage	V _{CEO}	45	25	25	V
Collector Emitter Voltage	V _{CES}	50	30	30	V
Emitter Base Voltage	V _{EBO}	6.0	5.0	5.0	V
Collector Current Continuous	I _C	100			mA
Power Dissipation at T _a =25°C	P _D	350			mW
Derate Above 25°C		2.8			mW/°C
Power Dissipation at T _c =25°C	P _D	1.0			W
Derate Above 25°C		8.0			mW/°C
Operating And Storage Junction Temperature Range	T _j , T _{stg}	- 55 to +150			°C

THERMAL RESISTANCE


Junction to Ambient in free air	R _{th (j-a)}	357	°C/W
Junction to Case	R _{th (j-c)}	125	°C/W

ELECTRICAL CHARACTERISTICS (T_a=25°C unless specified otherwise)

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	MAX	UNITS
Collector Emitter Voltage	V _{CEO}	I _C =2mA, I _B =0			
		BC237	45		V
		BC238/BC239	25		V
Emitter Base Voltage	V _{EBO}	I _E =10μA, I _C =0			
		BC237	6.0		V
		BC238/BC239	5.0		V
Collector Cut Off Current	I _{CES}	BC238/BC239		15	nA
		V _{CE} =30V, V _{BE} =0			
		BC237		15	nA
		V _{CE} =50V, V _{BE} =0			
		BC238/BC239		4.0	μA
		V _{CE} =30V, V _{BE} =0, T _a =125°C			
		BC237		4.0	μA
		V _{CE} =50V, V _{BE} =0, T _a =125°C			

NPN SILICON PLANAR EPITAXIAL TRANSISTORS

BC237,238, A,B,C
BC239, B,C



TO-92
Plastic Package
For Lead Free Parts, Device
Part # will be Prefixed with
"T"

ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$ unless specified otherwise)

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	MAX	UNITS	
DC Current Gain	h_{FE}	$I_C=10\mu\text{A}, V_{CE}=5\text{V}$				
		A		TYP90		
		B		TYP150		
		C		TYP270		
		$I_C=2\text{mA}, V_{CE}=5\text{V}$				
		BC237/238/239				
A		120	800			
B		120	220			
C		200	460			
		380	800			
		$*I_C=100\text{mA}, V_{CE}=5\text{V}$				
A			TYP120			
B			TYP180			
C			TYP300			
Collector Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=10\text{mA}, I_B=0.5\text{mA}$		0.20	V	
		$*I_C=100\text{mA}, I_B=5\text{mA}$		0.60	V	
		BC237/239		0.80	V	
		BC238				
Base Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C=10\text{mA}, I_B=0.5\text{mA}$		0.83	V	
		$*I_C=100\text{mA}, I_B=5\text{mA}$		1.05	V	
Base Emitter On Voltage	$V_{BE(on)}$	$I_C=2\text{mA}, V_{CE}=5\text{V}$	0.55	0.70	V	

SMALL SIGNAL CHARACTERISTICS

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	MAX	UNITS
Transistors Frequency	f_T	$I_C=0.5\text{mA}, V_{CE}=3\text{V}, f=100\text{MHz}$			
		BC237		TYP100	MHz
		BC238		TYP120	MHz
		BC239		TYP140	MHz
		$I_C=10\text{mA}, V_{CE}=5\text{V}, f=100\text{MHz}$	150		MHz
Collector Output Capacitance	C_{ob}	$V_{CB}=10\text{V}, I_E=0, f=1\text{MHz}$		4.5	pF
Emitter Input Capacitance	C_{ib}	$V_{EB}=0.5\text{V}, f=1\text{MHz}$		TYP8	pF
Noise Figure	NF	$V_{CE}=5\text{V}, I_C=0.2\text{mA}, R_S=2\text{K}\Omega,$ $f=1\text{KHz}, B=200\text{Hz}$		10	dB
		BC237/238 BC239		4.0	dB




*Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$

BC237_239Rev_1 201205E

TO-92
Plastic Package

For Lead Free Parts, Device Part #
will be Prefixed with "T"

TO-92 Leaded Plastic Package




DIM	Min	Max
A	4.32	5.33
B	4.45	5.20
C	3.18	4.19
D	0.40	0.55
E	0.30	0.55
F	5°	

All Dimensions are in mm

DIM	Min	Max
G	1.14	1.40
H	1.20	1.80
K	12.5	
L	1.982	2.082
M	1.03	1.53



Pin 1 Emitter
Pin 2 Base
Pin 3 Collector



TO-92
Plastic Package

For Lead Free Parts, Device Part #
will be Prefixed with "T"

TO-92 Tape and Ammo Packaging



All Dimensions are in mm

Tape Specifications

Item description	Symbol	TO-92			
		Min	Nom	Max	Tol
Body width	A1	4.45		5.20	
Body height	A	4.32		5.33	
Body thickness	T	3.18		4.19	
Pitch of component ^{Cr}	P		12.7		± 1.0
Feed hole pitch ^{S1}	Po		12.7		± 0.3
Feed hole center to component centre ^{S2}	P2		6.35		± 0.4
Comp. alignment, Side view ^{S3}	Dh		0	1.0	
Comp. alignment, Front view ^{S3}	Dh1		0	1.3	
Tape width ^{Cr}	W		18		± 0.5
Hold down tape width ^{Cr}	W0		6		± 0.2
Hole position	W1		9		+0.7 -0.5
Hold-down tape position	W2	0.0		0.7	
Lead wire clinch height	H0		16		± 0.5
Component height	H1			24.0	
Length of clipped leads	L			11.0	
Feed hole diameter ^{Cr}	Do		4		± 0.2
Total tape thickness ^{S4}	t			1.2	
Lead-to-lead distance ^{Cr}	F1, F2	2.4		2.7	
Stand off	H2	0.45		1.45	
Clinch height	H3			3.0	
Lead parallelism ^{Cr}	C1-C2			0.22	
Pull-out force	(p)	6N			

Taping Specification

- Maximum alignment deviation between leads not to be greater than 0.20 mm.
- Maximum non-cumulative variation between tape feed holes shall not exceed 1 mm in 20 pitches.
- Hold down tape not to exceed beyond the edge(s) carrier tape and there shall be no exposure of adhesive.
- No more than 3 consecutive missing components is permitted.
- A tape trailer, having at least three feed holes is required after the last component.
- Splices shall not interfere with the sprocket feed holes.

§1 Cumulative pitch error 1.0 mm/20 pitch.

§2 To be measured at bottom of clinch.

§3 At top of body.

§4 $t1 = 0.3 - 0.6$ mm

Cr Critical Dimension.

All Dimensions are in mm

Packaging Information

T & A: Tape and Ammo Pack; T & R: Tape and Red; Bulk: Loose in Poly bags; Tube: Tube and Ammo Pack; k: 1.000

Package/Case Type	Packaging Type	Std. Packing		Inner Carton		Outer Carton		
		Qty	Qty	Size L x W x H	Gross Weight	Qty	Size L x W x H	Gross Weight
				(cm)	(Kg)		(cm)	(Kg)
TO-92	Bulk	1,000	5K	19x19x8	1.10	80K	43x40x35	20.0
	T&A	2,000	2K	32x4.5x20	0.70	40K	43x40x35	15.20

Component Disposal Instructions

1. CDIL Semiconductor Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE).

Customer Notes

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone + 91-11-2579 6150, 4141 1112 Fax + 91-11-2579 5290, 4141 1119

email@cdil.com

www.cdilsemi.com