


**NPN SILICON PLANAR POWER TRANSISTOR**

**2N3773**



**TO-3  
Metal Can Package**

**Complementary 2N6609**

**General Purpose Amplifier specially suited for Power Conditioning Applications**

**ABSOLUTE MAXIMUM RATINGS**

DESCRIPTION	SYMBOL	VALUE	UNITS
Collector Base Voltage	$V_{CBO}$	160	V
Collector Emitter Voltage	$V_{CEO}$	140	V
Collector Emitter Voltage	$V_{CEX}$	160	V
Emitter Base Voltage	$V_{EBO}$	7	V
Collector Current Continuous	$I_C$	16	A
Peak (1)		30	A
Base Current Continuous	$I_B$	4	A
Peak (1)		15	A
Power Dissipation @ $T_c=25^\circ\text{C}$	$P_D$	150	W
Derate Above 25°C		0.855	W/°C
Operating and Storage Junction Temperature Range	$T_j, T_{stg}$	- 65 to +200	°C

**THERMAL RESISTANCE**

Junction to Case	$R_{th(j-c)}$	1.17	°C/W
------------------	---------------	------	------


(1) Pulse Test: Pulse Width =5ms, Duty Cycle ≤10%

**ELECTRICAL CHARACTERISTICS ( $T_c=25^\circ\text{C}$  unless specified otherwise)**

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	MAX	UNITS
Collector Emitter Sustaining Voltage	$V_{CEO(sus)}$ *	$I_C=0.2A, I_B=0$	140		V
Collector Emitter Sustaining Voltage	$V_{CEX(sus)}$ *	$I_C=0.1A, R_{BE}=100\Omega, V_{BE(off)}=1.5V$	160		V
Collector Emitter Sustaining Voltage	$V_{CER(sus)}$ *	$I_C=0.2A, R_{BE}=100\Omega$	150		V
Collector Cut Off Current	$I_{CEO}$	$V_{CE}=120V, I_B=0$		10	mA
Collector Cut Off Current	$I_{CEX}$	$V_{CE}=140V, V_{BE(off)}=1.5V$ $T_c=150^\circ\text{C}$ $V_{CE}=140V, V_{BE(off)}=1.5V$		2.0	mA
Collector Cut Off Current	$I_{CBO}$	$V_{CB}=140V, I_E=0$		2.0	mA
Emitter Cut Off Current	$I_{EBO}$	$V_{BE}=7V, I_C=0$		5.0	mA
DC Current Gain	$h_{FE}$ *	$I_C=8A, V_{CE}=4V$ $I_C=16A, V_{CE}=4V$	15 5	120	
Collector Emitter Saturation Voltage	$V_{CE(sat)}$ *	$I_C=8A, I_B=800mA$ $I_C=16A, I_B=3.2A$		1.4 4.0	V
Base Emitter on Voltage	$V_{BE(on)}$ *	$I_C=8A, V_{CE}=4V$		2.2	V

# NPN SILICON PLANAR POWER TRANSISTOR

2N3773



TO-3  
Metal Can Package

## ELECTRICAL CHARACTERISTICS ( $T_C=25^{\circ}\text{C}$ unless specified otherwise)

### Dynamic Characteristics


DESCRIPTION	SYMBOL	TEST CONDITION	MIN	MAX	UNITS
Magnitude of Common Emitter Small Signal, Short Circuit, Forward Current Transfer Ratio	$ h_{fe} $	$I_C=1\text{A}$ , $f=50\text{KHz}$	4.0		
Small Signal Current Gain	$h_{fe}$	$I_C=1\text{A}$ , $V_{CE}=4\text{V}$ , $f=1\text{KHz}$	40		

### Second Breakdown Characteristics


DESCRIPTION	SYMBOL	TEST CONDITION	MIN	MAX	UNITS
Second Breakdown Collector Current With Base Forward Biased	$I_{S/b}$	$V_{CE}=100\text{V}$ , $t=1.0\text{ s}$ , Nonrepetitive	1.5		A

\*Pulse Test: Pulse Width =300ms, Duty Cycle  $\leq$ 2%

CHARACTERISTICS PLOTS




TO-3 Metal Can Package



DIM	MIN.	MAX.
A	—	39.37
B	—	22.22
C	6.35	8.50
D	0.96	1.09
E	—	1.77
F	29.90	30.40
G	10.69	11.18
H	5.20	5.72
J	16.64	17.15
K	11.15	12.25
L	—	26.67
M	3.84	4.19

All dimensions in mm.



PIN CONFIGURATION

1. BASE
2. EMITTER
3. COLLECTOR

Packing Detail

PACKAGE	STANDARD PACK		INNER CARTON BOX		OUTER CARTON BOX		
	Details	Net Weight/Qty	Size	Qty	Size	Qty	Gr Wt
TO-3	100 pcs/pkt	1.3 kg/100 pcs	12.5" x 8" x 1.8"	0.1K	17" x 11.5" x 21"	2K	27.5 kgs

### Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD is believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of  
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.  
Telephone + 91-11-2579 6150, 5141 1112 Fax + 91-11-2579 5290, 5141 1119  
email@cdil.com www.cdil.com