



CAMBLOCK PLUS

5mm Pitch Double Decker Rising Clamp Terminal Blocks

CTBPDDVG

- Double interlocking mechanism for increased strength
- Double decker
- Moulded in green UL94-V0 flame retardant PA66
- Professional rising clamp terminals
- 2.5mm² (30-12AWG)
- Guided pin alignment
-   approved



SPECIFICATION

| | |
|---------------------------|-------------------------------|
| Rating | UL=15A/300V, VDE=18A/250V |
| Insulation resistance | 500MΩ/500V |
| Withstand Voltage | AC2000V/1min |
| Contact Resistance | 20mΩ (max) |
| Working Temperature | -40°C to 105+°C |
| Mouldings | UL94-V0 Flame retardant PA66 |
| Pin/Terminal | Tin plated brass |
| Rising Clamp | Brass, nickel plated |
| Screw/Torque | M2.5 Steel, zinc plated 0.4Nm |
| Recommended PCB hole size | ø1.5mm |

| TYPE NO. | POLES | LENGTH |
|-------------|-------|--------|
| CTBPDDVG/2 | 4 | 12.5mm |
| CTBPDDVG/3 | 6 | 17.5mm |
| CTBPDDVG/4 | 8 | 22.5mm |
| CTBPDDVG/5 | 10 | 27.5mm |
| CTBPDDVG/6 | 12 | 32.5mm |
| CTBPDDVG/7 | 14 | 37.5mm |
| CTBPDDVG/8 | 16 | 42.5mm |
| CTBPDDVG/9 | 18 | 47.5mm |
| CTBPDDVG/10 | 20 | 52.5mm |
| CTBPDDVG/11 | 22 | 57.5mm |
| CTBPDDVG/12 | 24 | 62.5mm |

