


Proximity Switch - Reed Switch based - Rectangular - Normally Open Contacts
Part Number : CTC012 Suggested Magnet: CTCM
Product Data Sheet

PICTURE



DIMENSIONS



Drawings not to scale
 All dimensions in mm nominal

✓ RoHS Compliant

SPECIFICATION

Contact Form / Style	Normally Open
Switching Voltage	200 Vac
Switching Current	0.5 A
Switching Capacity (Resistive)	10 VA
Switching Distance	10.0 mm Minimum
Operating Temperature - Continuous	-20°C +85°C
Operating Temperature - Intermittent	-25°C +85°C
Storage temperature	-25°C +85°C
Case Material	Aluminium
Cable	2 x 0.14mm ² PVC Covered

Applications Include

- Position and limit sensing.
- Linear actuators.
- Security system switch.
- Door Switch.

Options

- Custom cable lengths, strip lengths, cable types, terminations.
- Higher Switching Voltage available.
- If you do not see what you need, just ask, as there is a strong possibility we can do it !

Did you know we also sell?



Rev. No.	Revision Note	Date	Signature
1	First Issue	19-07-06	NG

FORM AE043 ISS.2



As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.

Phone : +44 (0)1255 862236

www.assemtech.co.uk

Fax: +44 (0)1255 862014