



**FOWX2.E184650**

**Across-the-line Capacitors, Antenna-coupling Components, Line-bypass Components and Fixed Capacitors for Use in Electronic Equipment**

[Page Bottom](#)

**Across-the-line Capacitors, Antenna-coupling Components, Line-bypass Components and Fixed Capacitors for Use in Electronic Equipment**

[See General Information for Across-the-line Capacitors, Antenna-coupling Components, Line-bypass Components and Fixed Capacitors for Use in Electronic Equipment](#)

JENN FU ELECTRONICS CORP  
 16 LANE 256 HAI-WEI RD  
 CHUNG-HO HSIANG  
 SHING LUNG CHING  
 TAICHUNG, 434 TAIWAN

E184650

Type	V Rating	Capacitance Rating or Range	Series Resistance Rating or Range	Spark GAP
Across-the-line capacitors.				
MPX#	250; ac	0.0047 to 1.0 uF	—	—

#Suitable for use with special enclosure only.

**Fixed Capacitors**

Type Dsg	Capacitor Class	Voltage Rating (V)	Capacitance (µF) (Tolerance)	Resistance for RC Devices (ohms)	Lower Temp (°C)	Upper Temp (°C)
MPX	X2	250/275/310 Vac	0.001uF - 1uF, +/-20%##	—	-40	+100

##: the capacitance tolerance may be J for +/-5%, K for +/-10% or M for +/-20%.

Marking: Company name or trademarks "JF" or "JEFU" and type designation on product.

Last Updated on 2011-10-06

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2011 Underwriters Laboratories Inc.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety