



MATERIAL

Insulator : NYLON 66, UL94 V-2

Contact Pin : Brass

Contact Plated : Tin Plated

742-7 5 - xx W 001
 1 2 3 4 5

- 1. 5: Normal parts
- 7: Green Product
- 9: Green Product High Temp
- 2. 5: 2542H
- 3. No. of contacts per row
- 4. S: Crystal insulator
- W: White insulator
- 5. Pinrex internal code.

CIRCUITS	DIM A	DIM B
2	5.64	2.54
3	8.16	5.08
4	10.72	7.62
5	13.30	10.16
6	15.78	12.70
7	18.40	15.24
8	20.80	17.78
9	23.50	20.32
10	26.00	22.86
11	28.50	25.40
12	31.00	27.94
13	33.50	30.48
14	36.00	32.02
15	38.50	35.56
16	41.20	38.10
17	43.60	40.64
18	46.32	43.18
19	48.80	45.72
20	51.34	48.26

		TOLERANCE		 UNITS : mm		OLD PART NO. 2542H-xxW		TITLE MOLEX 2.54mm HOUSING	
		.0 =±.30		SCALE		SHEET		NEW PART NO.	
		.00 =±.20		NONE		1 OF 1		742-75-xxW001	
		.000 =±.XXX		SIZE		REV.		DRAW NO.	
B Revision		2008/01/21		A4		1		742-75-xxW001(B版)	
A RELEASE		2005/02/21				B			
REV. DESCRIPTION		DATE							
				ANG.=±3'				頻銳科技股份有限公司 PINREX TECHNOLOGY CORP.	